

# SDL Dock Lift

Pit Mounted  
**LOADWARRIOR® SERIES**

## LIFT PRODUCTS SPECIFICATIONS

4,000 - 8,000 LBS. CAPACITIES



### Design Highlights

- High Tensile Strength, Structural Tubing Construction for Maximum Stability
- Dual Lifting Cylinders for Optimum Performance
- Velocity Fuses on Lift Cylinders Prevent Lift from Free Falling in the Event of Hydraulic Failure
- Pre-wired NEMA-4X Push Button Control Panel
- Versatile, Split Entry Plates with Lifting Chains
- Removable, Mandrel Formed Tubing Handrails
- Maintenance Strut
- Removable Lifting Lugs
- Meets ANSI MH29.1 Safety Requirements for Industrial Scissor Lifts
- Upper Travel Limit Switch
- Oil Sight Gauge in Hydraulic Reservoir
- Self-lubricating Bushings
- Standard 25' Hydraulic Hose
- Low Temperature Oil
- Two-year Parts, One-year Labor Limited Warranty
- UL Approved Panel

### Available Options

- Electric Toe Guards
- Aluminum Bridge Plates
- Post Office Option Package
- Hot Dipped Galvanized
- Spring-assisted Bridge
- In-motion Warning Beeper and Flashing Light
- Roller Curtains
- Accordion Bellow Skirting
- Hydraulic Pop-up Stop
- Mechanical Pop-up Stop
- Hydraulic Lip
- Biodegradable Oil
- Special Sizes
- Other \_\_\_\_\_

### Project Information

Job Name \_\_\_\_\_

Address \_\_\_\_\_

General Contractor \_\_\_\_\_

Distributor \_\_\_\_\_

Model \_\_\_\_\_ Quantity \_\_\_\_\_ Voltage/Phase \_\_\_\_\_



1612 Hutton Drive, Suite 140 • Carrollton, TX 75006, USA • Tel: 800-933-4834 • Fax: 972-389-4769 • Email: sales@sercocompany.com • www.sercocompany.com

A continuing research program is in effect at Serco. We reserve the right to incorporate product improvement at any time without prior notice.

© 2011 4Front Engineered Solutions, Inc.

Form#: SPS-LDDL-0311

# SDL Dock Lift

## Pit Mounted LOADWARRIOR® SERIES

### LIFT PRODUCTS SPECIFICATIONS

4,000 - 8,000 LBS. CAPACITIES

Model No.	Travel [in]	Capacity [lb]	Standard Platform [in]	Max. End Load [lb]	Max. Side Load [lb]	Lowered Height [in]	HP	Raise Lower Speed [fpm]	Ship Wt. [lb]
SDL48-4	60	4,000	48 x 96	3,000	2,000	12	5	16	2,450
SDL48-5	60	5,000	48 x 96	3,750	2,500	12	5	15	2,550
SDL48-6	60	6,000	48 x 96	4,500	3,000	12	5	15	2,575
SDL48-8	60	8,000	48 x 96	6,000	4,000	14	5	10	2,320
SDL58-4	60	4,000	60 x 96	3,000	2,000	12	5	16	2,400
SDL58-5	60	5,000	60 x 96	3,750	2,500	12	5	15	2,400
SDL58-6	60	6,000	60 x 96	4,500	3,000	12	5	15	2,450
SDL58-8	60	8,000	60 x 96	6,000	4,000	14	5	10	3,700
SDL68-5	60	5,000	72 x 96	3,750	2,500	12	3	12	2,850
SDL68-6	60	6,000	72 x 96	4,500	3,000	12	5	15	2,900
SDL68-8	60	8,000	72 x 96	6,000	4,000	14	5	10	2,350
SDL69-4	60	4,000	72 x 108	3,000	2,000	12	5	16	2,850
SDL69-5	60	5,000	72 x 108	3,750	2,500	12	3	12	2,950
SDL69-6	60	6,000	72 x 108	4,500	3,000	12	5	15	3,070
SDL69-8	60	8,000	72 x 108	6,000	4,000	14	5	10	4,000
SDL610-5	60	5,000	72 x 120	3,750	2,500	12	3	12	3,050
SDL610-6	60	6,000	72 x 120	4,500	3,000	12	5	15	3,150
SDL610-8	60	8,000	72 x 120	6,000	4,000	14	5	10	3,150
SDL78-4	60	4,000	84 x 96	3,000	2,000	12	5	16	2,710
SDL78-5	60	5,000	84 x 96	3,750	2,500	12	5	15	2,750
SDL78-6	60	6,000	84 x 96	4,500	3,000	12	5	15	2,825
SDL78-8	60	8,000	84 x 96	6,000	4,000	14	5	10	4,000
SDL79-5	60	5,000	84 x 108	3,750	2,500	12	5	15	2,860
SDL79-6	60	6,000	84 x 108	4,500	3,000	12	5	15	2,925
SDL79-8	60	8,000	84 x 108	6,000	4,000	14	5	10	4,200
SDL710-5	60	5,000	84 x 120	3,750	2,500	12	5	15	2,900
SDL710-6	60	6,000	84 x 120	4,500	3,000	12	5	15	2,900
SDL710-8	60	8,000	84 x 120	6,000	4,000	14	5	10	4,360
SDL88-5	60	5,000	96 x 96	3,750	2,500	12	3	12	2,850
SDL88-6	60	6,000	96 x 96	4,500	3,000	12	5	15	2,940
SDL88-8	60	8,000	96 x 96	6,000	4,000	14	5	10	4,170
SDL89-5	60	5,000	96 x 108	3,750	2,500	12	5	15	2,920
SDL89-6	60	6,000	96 x 108	4,500	3,000	12	5	15	3,000
SDL89-8	60	8,000	96 x 108	6,000	4,000	14	5	10	4,360
SDL810-5	60	5,000	96 x 120	3,750	2,500	12	3	12	3,150
SDL810-6	60	6,000	96 x 120	4,500	3,000	12	5	15	3,150
SDL810-8	60	8,000	96 x 120	6,000	4,000	14	5	10	4,540

